GP-KJ1220 Flat Laminated Wall Panels

Product Specification Schedule

Model & use	GP-KJ1220 flat laminated wall-panel model for interior passageway and background walls
Selected configuration	GP-KJ1220 flat laminated wall panel; the order pairs one confirmed substrate with its selected thickness and surface reference
Listed face format	1220 mm width x 2600 mm length
Listed thickness selection	5 mm or 8 mm; selected thickness paired with the confirmed substrate in the order
Substrate identification	Bamboo-fiber composite, WPC or OSB description as confirmed for the selected configuration; one named substrate retained in the quotation
Listed process	Surface lamination, hot and cold pressing, and side slotting
Wall & supply details	Pattern direction, joint and edge details, cutouts, backing, attachment, sheet quantities and trims

Flat wall panel configuration

GP-KJ1220 / project specification: GP-KJ1220 flat laminated wall panel; the order pairs one confirmed substrate with its selected thickness and surface reference

GP-KJ1220 Wall Sheet Supply Schedule

Panel configuration: GP-KJ1220 sheets, one confirmed substrate, selected thickness, laminated finish and quantity

Sheet preparation: Cut pieces, pattern direction, openings and agreed exposed-edge treatments

Supporting package: Requested trims, backing, attachment materials and interface components separately itemized

Delivery & site work: Packing and freight; factory preparation, wall preparation and installation separately stated

Configuration basis and sources

Indoor WPC Wall Panel - GP-KJ1220 - https://www.georgepanel.com/product-item/plane-plate-wall-panel/