Wall-Mounted Folding Pot Filler with Dual Shutoffs

Product Specification Schedule

Fixture type	Wall-mounted articulated pot filler with two folding swing joints and separate base/outlet shutoffs
Selected configuration	Wall-mounted folding swing-arm pot filler with shutoffs at the base and spout; selected warm metal-tone appearance.
Selected reach basis	24 in, approximately 610 mm; actual wall-pivot-to-outlet reach and folded projection scheduled separately
Operating controls	Two shutoffs at base and spout; half-turn ceramic valve controls in the selected package
Movement dimensions	Wall-pivot height, outlet height, vertical arm offset and folded/extended envelope in mm
Mounting interface	Actual wall connection, supporting substrate, finished backsplash thickness and trim/fixing arrangement
Water & supplied parts	Connection standard, water conditions and required backflow/isolation components identified for the installation; body alloy and finish process separately specified

Pot-filler configuration

Dual-Joint Wall Mount / Dual Shutoff: Wall-mounted folding swing-arm pot filler with shutoffs at the base and spout; selected warm metal-tone appearance.

Pot Filler, Wall Interface & Separate Plumbing Scope

Articulated fixture: Two-joint arm, wall-side base, outlet, base/spout shutoffs and selected visible surface.

Mounting parts: Actual wall trim and supplied fixing/connection parts, matched to the assembly.

Separate plumbing: Supply rough-in, supporting wall, isolation/backflow items and local installation separately identified.

Delivery package: Quantity, protected joints/controls, destination and receiving arrangements.

Configuration basis and sources

Pot Filler Faucet | Swing-Arm Stove Convenience - https://georgesolution.com/product/pot-filler-faucet/