Solid-Door Hotel Minibar Fridge with a Key Lock

Product Specification Schedule

Selected appliance	Hotel minibar refrigerator; refrigeration-only compartment
Configuration options	40 L selected capacity 400 W x 450 D x 550 H mm; 30 L selected capacity 380 W x 430 D x 480 H mm; 50 L selected capacity 450 W x 480 D x 600 H mm
Selected exterior	Powder-coated sheet steel; charcoal
Selected interior	White liner, two shelf levels and a door pocket
Door and access	Solid right-hinged door, recessed pull and mechanical key lock
Selected electrical version	230 V / 50 Hz; destination plug and equipment documents separately specified
Installation interface	Ventilation route, open-door sweep and furniture opening coordinated
Supply unit	Refrigerator body and listed fittings; joinery and beverages excluded

Capacity and closed-body fit

40 L minibar: 40 L selected capacity 400 W x 450 D x 550 H mm

30 L minibar: 30 L selected capacity 380 W x 430 D x 480 H mm

50 L minibar: 50 L selected capacity 450 W x 480 D x 600 H mm

Hotel Minibar Equipment Schedule

Capacity and fit: Selected nominal capacity, closed-body dimensions, room reference and unit quantity.

Cabinet and interior: Charcoal exterior, solid door, lock, hinge side, shelves and pocket.

Project interfaces: Electrical version, plug, cabinet opening, ventilation route and door swing.

Delivery boundary: Packing, destination and handling scope; surrounding joinery and installation separately listed.