Fiberglass Entry Door with Two Frosted Sidelights

Product Specification Schedule

Selected system	Single fiberglass leaf with two framed frosted-glass sidelights
Configuration options	405 mm sidelight modules 1810 W x 2090 H mm outer frame; 360 mm sidelight modules 1720 W x 2090 H mm outer frame; 450 mm sidelight modules 1900 W x 2090 H mm outer frame
Selected leaf	915 W x 2032 H x 45 T mm
Selected leaf section	2 mm FRP +41 mm polyurethane core +2 mm FRP
Central frame module	1000 mm wide; outer-frame height 2090 mm
Selected appearance	White woodgrain-textured two-panel face; frosted sidelights
Selected hardware scope	Black lever/deadbolt; hinges, keying, sill and seals separately scheduled
Project interface	Rough opening, glass safety, anchors, wall junctions and performance documents separately specified

Sidelight module and overall frame

405 mm sidelights: 405 mm sidelight modules 1810 W x 2090 H mm outer frame

360 mm sidelights: 360 mm sidelight modules 1720 W x 2090 H mm outer frame

450 mm sidelights: 450 mm sidelight modules 1900 W x 2090 H mm outer frame

Fiberglass Entry Assembly Order Schedule

Door and frame: Leaf 915 x 2032 x 45 mm; central module 1000 mm; selected sidelight widths and frame height.

Glazing and finish: Two frosted sidelight units, actual glass build, white textured leaf/frame and sample reference.

Hardware and interfaces: Lever/deadbolt, hinges, keying, sill/seals, rough opening and wall junctions.

Supply boundary: Opening references, handing, quantities, packing and destination; site work separately listed.