Flamed Gray Granite Paving Slabs with Sawn Edges

Product Specification Schedule

Selected stone	Natural gray granite with granular mineral appearance
Configuration options	600 L x 300 W x 30 T mm flamed gray granite; 300 L x 300 W x 30 T mm flamed gray granite; 600 L x 600 W x 30 T mm flamed gray granite
Selected slab thickness	30 mm nominal
Selected top finish	Flamed
Selected edges	Sawn straight; special exposed-edge treatment separately scheduled
Selected joint	5 mm; installed module adds joint allocation to stone face
Net face areas	600 x 300:0.18 m2;300 x 300:0.09 m2;600 x 600:0.36 m2, excluding joints/waste
Project boundary	Bedding, drainage, traffic design, edge restraints and required stone test documents separately specified

Face format and stone thickness

600 x 300 mm slabs: 600 L x 300 W x 30 T mm flamed gray granite

300 x 300 mm slabs: 300 L x 300 W x 30 T mm flamed gray granite

600 x 600 mm slabs: 600 L x 600 W x 30 T mm flamed gray granite

Granite Paving Slab Order Schedule

Stone pieces: Face dimensions, 30 mm thickness, piece counts, net stone area and cut references.

Material and finish: Accepted gray granite range, flamed top, sawn edges and special edge work.

Project interfaces: Paving modules, joints, bedding, drainage, traffic requirements and perimeter details.

Delivery boundary: Pallet labels, protection, destination and unloading;site materials/work separately listed.