Interlocking Porcelain Deck Tiles on Drainage Grids

Product Specification Schedule

Selected assembly	Porcelain face on a polypropylene interlocking drainage grid
Configuration options	300 x 300 mm porcelain face 20 mm tile +10 mm clip grid; 600 x 300 mm porcelain face 20 mm tile +10 mm matched clip grid; 600 x 600 mm porcelain face 20 mm tile +10 mm matched clip grid
Selected porcelain	20 mm thick;gray stone-look textured face
Selected clip grid	10 mm black polypropylene;matched ribs and interlocking edge tabs
Selected assembled thickness	30 mm =20 mm tile +10 mm grid
Net porcelain face areas	300 x 300:0.09 m2;600 x 300:0.18 m2;600 x 600:0.36 m2
Dimension boundary	Face dimensions exclude tab projections and assembled layout joints
Project boundary	Supporting base, drainage, edges, waterproofing and required complete-assembly evidence separately specified

Porcelain face and matched grid format

300 x 300 mm module: 300 x 300 mm porcelain face 20 mm tile +10 mm clip grid

600 x 300 mm module: 600 x 300 mm porcelain face 20 mm tile +10 mm matched clip grid

600 x 600 mm module: 600 x 600 mm porcelain face 20 mm tile +10 mm matched clip grid

Interlocking Porcelain Deck Tile Order Schedule

Modules: Selected face formats, complete module counts, net porcelain area and cut schedule.

Assembly: Gray porcelain 20 mm, polypropylene grid 10 mm, matched clips and accepted sample reference.

Interfaces: Base support, drainage, waterproofing, perimeter trims and transition details.

Delivery scope: Format labels, protected packing, destination and spares;site preparation/installation separately listed.