Textured Through-Body Gray Porcelain Pool-Floor Mosaic

Product Specification Schedule

Selected material	Gray textured matte unglazed through-body porcelain on mesh
Configuration options	144 gray unglazed chips 300 x 300 mm installed module; 48 gray unglazed chips 100 x 300 mm installed module; 24 gray unglazed chips 50 x 300 mm installed module
Selected chip	23 x 23 x 6 mm square
Selected joint	2 mm clear gap; 25 mm chip-and-joint pitch
Field sheet	12 x 12 =144 chips; 298 x 298 mm face; 300 x 300 mm installed module
Border and edge strips	4 x 12 =48 chips:98 x 298 face/100 x 300 module; 2 x 12 =24 chips:48 x 298 face/50 x 300 module
Installed module areas	Field 0.09 m2; border 0.03 m2; edge 0.015 m2, including joint allocation
Pool assembly boundary	Actual slip/immersion evidence, mesh contact, waterproofing, adhesive, grout and movement joints separately specified

Mesh format and installed module

12 x 12 field sheet: 144 gray unglazed chips 300 x 300 mm installed module

4 x 12 border strip: 48 gray unglazed chips 100 x 300 mm installed module

2 x 12 edge strip: 24 gray unglazed chips 50 x 300 mm installed module

Pool-Floor Porcelain Mosaic Order Schedule

Formats: Field 144, border 48 and edge 24 chip formats; piece/module counts and pool-zone references.

Material: 23 x 23 x 6 mm unglazed textured gray chips, 2 mm joints and accepted shade/texture range.

Assembly: Mesh/backing compatibility, adhesive contact, waterproofing, grout, drains and movement joints.

Delivery boundary: Spare formats, protected packing, destination and separately assigned installation/material scope.