Wand-Operated Vertical Blinds for Sliding Glass Doors

Product Specification Schedule

Selected system	Vertical rotating vanes on a white aluminum headrail
Configuration options	127 mm white PVC vanes manual wand one-way draw; 89 mm white PVC vanes manual wand one-way draw; 127 mm ivory polyester fabric vanes manual wand one-way draw
Selected finished blind size	3000 W x 2400 H mm; opening and mounting overlap separately recorded
Selected operation	Manual wand with compatible tilt/traverse mechanism
Selected draw arrangement	One-way draw to left side
Selected lower components	Vane bottom weights and connecting links
Vane alternatives	89 mm white PVC or 127 mm ivory polyester fabric on matched rail assemblies
Site interfaces	Final vane count/overlap/stack width, brackets, substrate fixings and floor/threshold clearance

Selected vane configuration

127 mm PVC vanes: 127 mm white PVC vanes manual wand one-way draw

89 mm PVC vanes: 89 mm white PVC vanes manual wand one-way draw

127 mm fabric vanes: 127 mm ivory polyester fabric vanes manual wand one-way draw

Sliding-Door Vertical Blind Quote Scope

Blind size: Finished width/height, site opening, mounting position and unit count

Vanes and rail: Material/width, carrier mix, weights, links and white aluminum rail

Operation and mounting: Manual wand, left-side draw, stack clearance, brackets and fixing scope

Delivery: Accepted sample, room references, spares, required documents, destination and delivery stages