Surface-Mounted Stainless Steel Shower Panels

Product Specification Schedule

Reference & selected construction	GEORGE D-070 family material/mounting reference; selected custom brushed 304 stainless wall panel. No factory D-070 dimensional or outlet-version mapping is asserted.
Configuration options	Selected custom 304 stainless panel: integral overhead spray and hand shower, manual temperature mixer, separate flow control and two-position outlet selector; one mode at a time.; Same selected panel size and manual controls, adding two perforated body-spray zones and a three-position selector; the two body zones operate together as one mode.
Panel & hood dimensions	Selected enclosure H1200 x W220 mm; body projection 110 mm; overhead maximum projection 400 mm; overhead spray face 220 x 250 mm.
Mounting setout	Panel bottom 850 mm and top 2050 mm above finished floor. Control centers: mixer 1200 mm, flow 1325 mm, mode selector 1450 mm. Holder center 1500 mm. Bracket/anchor pattern follows the approved assembly.
Supplied outlets & controls	Overhead spray + 1 hand shower + 1500 mm hose + holder; manual temperature mixer, separate flow control and 2-position selector. Body-spray option adds two zones and a 3-position selector, one mode at a time.
Body-spray option	Two 100 x 180 mm perforated zones centered at 1000 and 1700 mm above finished floor; both operate together in the third mode.
Water interfaces & qualification	Selected rear hot/cold inlet requirement: G1/2 parallel connections, 150 mm centers at 1000 mm above finished floor; hot left when facing panel. Matching valves/fittings and pressure/flow curves required for the assembly; no universal operating-pressure rating asserted.

Custom panel outlet package

Overhead + hand shower: Selected custom 304 stainless panel: integral overhead spray and hand shower, manual temperature mixer, separate flow control and two-position outlet selector; one mode at a time.

Overhead + hand shower + body sprays: Same selected panel size and manual controls, adding two perforated body-spray zones and a three-position selector; the two body zones operate together as one mode.

Shower Panel Assembly, Connections & Site Work

Selected custom panel: One brushed 304 enclosure with integral overhead spray, hand shower, 1500 mm hose, holder, manual mixer, flow control and selected 2- or 3-position outlet selector.

Mounting & connection parts: Panel support rails/brackets, named control components and rear inlet connectors; body-spray package additionally includes two perforated zones. Anchors and site adapters separately itemized.

Bathroom installation: Existing fitting removal, substrate preparation, pipework, waterproofing, tile repairs, installation and commissioning separately scoped.

Packing & delivery: Protected panel surfaces and separately packed small components; packing, freight destination and final delivery identified for the shipment.

Configuration basis and sources

Luxury 304 stainless steel back massage shower screen D-070/073/074/075 - https://georgebathroom.com/product/luxury-304-stainless-steel-back-massage-shower-screen-d-070-073-074-075/