YY8086-3W Louvered LED Step Light

Product Specification Schedule

Model reference	YY8086-3W
Visible configuration	YY8086-3W low-wall light with a black framed outer face and horizontal shielding at the luminous opening.
Product arrangement	Framed low-wall face with horizontal shielding across the light opening.
Power designation	3 W
Mounting interfaces	Face width and height, wall opening, fixing footprint and connection depth are separate dimensions.
Electrical package	Input supply, power components, light color and controls identified for the selected assembly.
Site application	Low vertical wall positions beside steps and pedestrian routes; exposure and supporting wall detailed for the location.

Fixture configuration

Black framed face / louvered opening: YY8086-3W low-wall light with a black framed outer face and horizontal shielding at the luminous opening.

YY8086-3W Fixture & Site-Work Scope

Named fixture: YY8086-3W in the selected face and application arrangement, with quantities by site reference.

Listed components: Actual housing, fixing and electrical components specified with the selected assembly.

Site interfaces: Wall or ground preparation, supporting construction, water management and cable routes as separate tasks.

Packing & installation: Protective packing and destination freight as quoted; site wiring, electrical connection and installation separately listed.

Configuration basis and sources

George Light Product Catalog, page59 - https://www.georgebuild.com/wp-content/uploads/2025/12/lights-product-catalog.pdf