PVC-Faced Gypsum Lay-In Ceiling Tiles

Product Specification Schedule

Panel construction	Gypsum core with white textured PVC face and reflective backing film
Configuration options	595 x 595 x 8 mm 600 x 600 mm grid module; 1195 x 595 x 8 mm 1200 x 600 mm grid module; 595 x 595 x 9.5 mm 600 x 600 mm grid module
Square tile sections	595 x 595 mm face in 8 mm or 9.5 mm overall thickness
Rectangular tile section	1195 x 595 x 8 mm
Nominal grid modules	600 x 600 mm square;1200 x 600 mm rectangle
Actual tile-face areas	Square 0.354025 m2; rectangle 0.711025 m2
Edge and support	Square lay-in edge on a 24 mm visible exposed T-grid flange
Supply unit	Individual panels by format/thickness; grid and suspension components itemized

Ceiling tile format

Square 8 mm: 595 x 595 x 8 mm 600 x 600 mm grid module

Rectangle 8 mm: 1195 x 595 x 8 mm 1200 x 600 mm grid module

Square 9.5 mm: 595 x 595 x 9.5 mm 600 x 600 mm grid module

PVC-Faced Ceiling Tile Order Configuration

Tiles: Format, thickness, PVC finish, room quantity and replacement allowance

Grid package: Module, tees, suspension, perimeter angles and supporting connections

Services: Cutouts, independent service supports and access locations

Delivery: Room labels, face/corner protection, packing and destination