Three-Leaf Stacking Glass Patio Doors

Product Specification Schedule

Door configuration	Three moving aluminum-framed glazed leaves on three parallel tracks
Configuration options	3600 W x 2400 H x 150 D mm frame 3 leaves stack left; 3600 W x 2400 H x 150 D mm frame 3 leaves stack right; 4500 W x 2400 H x 150 D mm frame 3 leaves stack left
Frame outside requirements	3600 or 4500 W x 2400 H x 150 D mm
Nominal leaf-width bases	1250 mm for 3600 mm frame;1550 mm for 4500 mm frame
Insulating glazing requirement	6 mm glass /12 mm sealed cavity /6 mm glass =24 mm
Visible frame finish	Matte-black aluminum with coordinated beads and seals
Operating assembly	Matched rollers, upper guides, interlocks, stops, pulls, locks and drained sill
Supply unit	One opening-numbered frame, three glazed leaves and matched track/hardware set

Frame and stack arrangement

3600 mm left stack: 3600 W x 2400 H x 150 D mm frame 3 leaves stack left

3600 mm right stack: 3600 W x 2400 H x 150 D mm frame 3 leaves stack right

4500 mm left stack: 4500 W x 2400 H x 150 D mm frame 3 leaves stack left

Stacking Patio Door Order Configuration

Opening set: Frame width/height/depth, stack hand, location and quantity

Glazed leaves: Three leaf references,24 mm glass build, finish and required documents

Interfaces: Running support, parking/clear passage, sill drainage, fixings and installation

Delivery: Opening labels, glass/profile protection, weights, access and destination