Tufted Hotel Bath Mat with Bonded Rubber Backing

Product Specification Schedule

Finished dimensions	600 x 900 mm, including the bound perimeter.
Configuration options	600 x 900 mm microfiber tufted face with 8 mm pile, 1.5 mm carrier/bond allowance and 1.5 mm rubber backing; 11 mm nominal finished thickness.; 600 x 900 mm microfiber tufted face with 12 mm pile, 1.5 mm carrier/bond allowance and 1.5 mm rubber backing; 15 mm nominal finished thickness.
Face material	Polyester microfiber tufted face; ivory color requirement.
Rubber backing	1.5 mm rubber below a 1.5 mm polyester carrier/bond allowance.
Default thickness	8 mm pile +1.5 mm carrier/bond +1.5 mm rubber =11 mm nominal finished thickness.
Higher-pile thickness	12 mm pile +1.5 mm carrier/bond +1.5 mm rubber =15 mm nominal finished thickness.
Edge construction	Matching bound perimeter around the finished mat.
Approval & supply unit	Complete laundry-process sample; bulk quantities counted as individual finished mats.

Bath mat pile configuration

8 mm Pile: 600 x 900 mm microfiber tufted face with 8 mm pile, 1.5 mm carrier/bond allowance and 1.5 mm rubber backing; 11 mm nominal finished thickness.

12 mm Pile: 600 x 900 mm microfiber tufted face with 12 mm pile, 1.5 mm carrier/bond allowance and 1.5 mm rubber backing; 15 mm nominal finished thickness.

Backed Bath Mat Supply Schedule

Mats: Individual 600 x 900 mm finished mats, split by 8 or 12 mm pile.

Construction: Microfiber tufted face, polyester carrier/bond layer, rubber backing and bound edge.

Approval: Complete sample through the property laundry process.

Packing: Pile code, size, finished mat count and delivery-lot label.