Aluminum Reducer Strips for Unequal Floor Levels

Product Specification Schedule

Cover width	60 mm inclined cover.
Configuration options	60 mm-wide inclined aluminum cover for a 3 mm finished-level difference; 1.5 mm nominal cover thickness and matched concealed fixing track.; 60 mm-wide inclined aluminum cover for a 6 mm finished-level difference; 1.5 mm nominal cover thickness and matched concealed fixing track.; 60 mm-wide inclined aluminum cover for a 9 mm finished-level difference; 1.5 mm nominal cover thickness and matched concealed fixing track.
Bar length	2700 mm cover and matched fixing-track length basis.
Nominal cover thickness	1.5 mm aluminum.
Fixing track	18 W x 10 H mm concealed aluminum track with central clip engagement.
Joint recess	20 mm clear width and 12 mm depth below the lower finished-floor datum.
Visible finish	Satin-silver aluminum with eased exposed lips.
Cut schedule	Opening references, finished lengths, 3/6/9 mm rise codes and substrate fixing detail.

Finished-floor level difference

3 mm Level Difference: 60 mm-wide inclined aluminum cover for a 3 mm finished-level difference; 1.5 mm nominal cover thickness and matched concealed fixing track.

6 mm Level Difference: 60 mm-wide inclined aluminum cover for a 6 mm finished-level difference; 1.5 mm nominal cover thickness and matched concealed fixing track.

9 mm Level Difference: 60 mm-wide inclined aluminum cover for a 9 mm finished-level difference; 1.5 mm nominal cover thickness and matched concealed fixing track.

Reducer Cover & Track Supply Schedule

Profiles: 60 mm cover and matched track by rise code and length.

Cuts: Finished opening lengths and end-condition schedule.

Fixing: Recess preparation and substrate-specific track fixing items.

Packing: Protected metal faces with opening, rise and cut-length labels.