Openwork Oak Lattice Wall Art Triptych

Product Specification Schedule

Decorative construction	Solid-oak open diamond lattice in matching perimeter frames
Configuration options	3 x 400 x 900 mm panels 50 mm gaps 1300 mm group width; 2 x 400 x 900 mm panels 50 mm gap 850 mm group width; 1 x 400 x 900 mm panel 400 mm overall width
Individual framed panel	400 W x 900 H x 30 D mm; cleat stand-off additional
Lattice section	18 mm depth; 8 mm diagonal rib width
Diamond pitch	40 mm
Display gaps and set widths	50 mm between frames; one/pair/triptych widths 400 / 850 / 1300 mm
Hanging interface	Concealed upper cleat; anchors coordinated with wall substrate and complete panel
Supply unit	Chosen set of framed oak panels with individual cleats and scheduled fixing package

Panel set

Three-panel set: 3 x 400 x 900 mm panels 50 mm gaps 1300 mm group width

Two-panel set: 2 x 400 x 900 mm panels 50 mm gap 850 mm group width

Single panel: 1 x 400 x 900 mm panel 400 mm overall width

Oak Lattice Wall Art Order Configuration

Arrangement: Panel count, room elevation, gaps and wall margins

Oak work: Lattice, frame depth, grain and matte-finish reference

Wall connection: Cleats, anchors, substrate and installation scope

Delivery: Panel sequence, individual protection and destination