Freestanding Oak-Veneered Lecterns with Sloped Reading Tops

Product Specification Schedule

Joinery material	18 mm oak-veneered plywood; clear matte finish
Configuration options	600 W x 450 D mm top 1050 front /1150 rear surface height; 500 W x 400 D mm top 1050 front /1150 rear surface height; 700 W x 500 D mm top 1050 front /1150 rear surface height
Reading-surface heights	1050 mm front; 1150 mm rear, from finished floor
Front document ledge	20 mm above the lower front reading surface
Main top rise	100 mm across 450 mm horizontal depth
Storage	One open shelf on the rear/speaker side
Main base	500 W x 400 D x 25 T mm steel-weighted base with floor pads
Supply unit	One lectern with sloped top, document ledge, rear shelf, base and pads

Reading-top footprint

600 x 450 mm top: 600 W x 450 D mm top 1050 front /1150 rear surface height

500 x 400 mm top: 500 W x 400 D mm top 1050 front /1150 rear surface height

700 x 500 mm top: 700 W x 500 D mm top 1050 front /1150 rear surface height

Oak Lectern Order Configuration

Lecterns: Top footprint, height datums, room reference and quantities

Woodwork: Oak veneer, 18 mm plywood, edges, ledge and shelf

Base and fittings: Steel base, pads, connections and equipment provisions

Delivery: Assembly format, finished-face protection, labels and destination