Top-Hung Vinyl Awning Windows

Product Specification Schedule

Frame and sash	White reinforced uPVC; 80 mm depth basis
Configuration options	1200 W x 900 H x 80 D mm one top-hung sash; 900 W x 600 H x 80 D mm one top-hung sash; 1500 W x 900 H x 80 D mm one top-hung sash
Operating layout	One top-hinged sash; lower edge opens outward
Opening basis	30 degrees from closed sash plane
Glazing build	6 mm glass +12 mm sealed airspace +6 mm glass =24 mm
Operating components	Top hinges, two side friction stays and low-center handle
Wall interface	Frame anchors, perimeter joint, sill drainage and wall finish by opening detail
Supply unit	One frame/sash/glazing unit with hinges, stays, handle, seals and fixing schedule

Outer-frame size

1200 x 900 mm: 1200 W x 900 H x 80 D mm one top-hung sash

900 x 600 mm: 900 W x 600 H x 80 D mm one top-hung sash

1500 x 900 mm: 1500 W x 900 H x 80 D mm one top-hung sash

Vinyl Awning Window Order Configuration

Windows: Outer size, opening number, quantity and travel space

Members and glass: White uPVC, reinforcement, 6/12/6 glazing, beads and seals

Operation: Top hinges, side stays, handle, restrictor and installation fixing

Delivery: Opening labels, corner/glass protection, packing and destination