Slotted Porcelain Pool Overflow Grating Tiles

Product Specification Schedule

Grate material	Textured gray porcelain; 25 mm body requirement
Configuration options	300 L x 250 D x 25 T mm six 180 mm through-slots; 300 L x 200 D x 25 T mm six 130 mm through-slots; 300 L x 300 D x 25 T mm six 230 mm through-slots
Common run length	300 mm
Slot pattern	Six through-slots, 10 mm wide with R5 ends
Slot-center layout	25 +50n mm along run length, n=0..5
Solid slot-end margins	35 mm at both depth ends
Pool-edge interface	Support seats, clear span, module joints and removable fit by channel detail
Supply unit	One removable grate tile; channel/support components itemized by pool run

Grate depth and slot length

250 mm depth /180 slot: 300 L x 250 D x 25 T mm six 180 mm through-slots

200 mm depth /130 slot: 300 L x 200 D x 25 T mm six 130 mm through-slots

300 mm depth /230 slot: 300 L x 300 D x 25 T mm six 230 mm through-slots

Pool Overflow Grate Order Configuration

Grates: Depth, slot length, run reference, module joints and counts

Ceramic: 25 mm porcelain, textured face, six slots and edge finish

Channel assembly: Support ledges, span, fit, restraints and drainage interfaces

Delivery: Orientation labels, slot/corner protection, counts and destination