Glue-Down SPC Vinyl Planks with Square Edges

Product Specification Schedule

Plank construction	SPC rigid-core vinyl with oak-print face and flat bondable rear
Configuration options	1200 L x 180 W x 3.5 T mm square-edge dryback SPC; 1000 L x 150 W x 3.5 T mm square-edge dryback SPC; 1500 L x 228 W x 3.5 T mm square-edge dryback SPC
Overall and wear thickness	3.5 mm overall, including 0.5 mm clear wear layer
Perimeter joint	Square edges on all four sides; direct-bond field layout
Gross face areas	1200 x 180: 0.216; 1000 x 150: 0.15; 1500 x 228: 0.342 m2
Adhesive interface	Compatible plank/rear/substrate system with application instructions
Floor coordination	Substrate preparation, row layout, transitions and separately scheduled adhesive layer
Supply unit	Carton of one dryback format; plank count, face coverage and adhesive package itemized

Plank format

1200 x 180 mm: 1200 L x 180 W x 3.5 T mm square-edge dryback SPC

1000 x 150 mm: 1000 L x 150 W x 3.5 T mm square-edge dryback SPC

1500 x 228 mm: 1500 L x 228 W x 3.5 T mm square-edge dryback SPC

Square-Edge SPC Order Configuration

Planks: Format, room area, carton piece count, cutting and spare quantity

Material: Oak-print face, 3.5 mm assembly, 0.5 mm wear layer and square edges

Floor assembly: Compatible adhesive, substrate condition, preparation and transition schedule

Delivery: Room labels, carton coverage, flat packing and destination