Stainless Steel U-Channels for Interior Glass Edges

Product Specification Schedule

Channel form	Open three-sided U section with equal-height legs and connecting base
Configuration options	304 brushed stainless 20 x 25 mm outside section 1.5 mm nominal wall 2400 mm length; Selected U-channel plus EPDM side gaskets, each with a 2.5 mm fitting target for 12 mm glass
Outside section	20 W x 25 H mm
Nominal metal wall and clear width	1.5 mm metal wall 17 mm nominal clear width
Selected material and finish	Grade 304 stainless steel brushed silver
Glass and side fitting targets	12 mm glass + two 2.5 mm EPDM side-gasket fitting targets
Straight bar length	2400 mm selected cutting basis
Supply unit	One selected straight channel bar, with side gaskets where chosen and scheduled caps/cuts/attachments

Stainless U-Channel Package

U-Channel Straight Bar: 304 brushed stainless 20 x 25 mm outside section 1.5 mm nominal wall 2400 mm length

U-Channel with Side Gaskets: Selected U-channel plus EPDM side gaskets, each with a 2.5 mm fitting target for 12 mm glass

Stainless Glass-Edge Channel Order Scope

Channel: 20 x 25 mm U section, 1.5 mm nominal wall and 2400 mm bar length

Gasket fit: 12 mm glass target, selected EPDM side profiles and fitting tolerances

Project detail: Retained edge, glass support, end caps, cuts, joints and channel attachments

Delivery: Opening references, quantities, finish protection and matched component packing