Bonnell Open-Coil Mattresses with Symmetric Padding

Product Specification Schedule

Core construction	150 mm connected hourglass Bonnell coil unit with helical lacing
Configuration options	1500 W x 2000 L x 220 T mm symmetric Bonnell build; 1800 W x 2000 L x 220 T mm symmetric Bonnell build; 1000 W x 2000 L x 220 T mm symmetric Bonnell build
Length and overall thickness	2000 L x 220 T mm
Symmetric layer stack	3 quilt / 30 PU / 2 felt / 150 springs / 2 felt / 30 PU / 3 quilt, mm
Each face padding	30 mm polyurethane foam over 2 mm felt insulation
Face and border textile	White polyester-knit quilting; gray polyester border; taped edges
Bed interface	Finished mattress footprint and base support arrangement by bed reference
Supply unit	One two-sided finished mattress with bed/room label and protective packing

Mattress width

1500 mm width: 1500 W x 2000 L x 220 T mm symmetric Bonnell build

1800 mm width: 1800 W x 2000 L x 220 T mm symmetric Bonnell build

1000 mm width: 1000 W x 2000 L x 220 T mm symmetric Bonnell build

Bonnell Mattress Order Configuration

Sizes: Width, 2000 mm length, 220 mm thickness and bed quantities

Build: Spring/lacing specification, mirrored foam/felt layers and quilting

Textiles: White face, gray border, edge tape and labels

Delivery: Wrapping, receiving route, storage arrangement and destination