Fixed-Post Corner Bifold Glass Door Sets

Product Specification Schedule

Door construction	Two perpendicular aluminum bifold runs, with two glazed leaves per run
Configuration options	2 +2 leaves 1740 mm outside leg dimensions 2480 mm overall height; 2 +2 leaves 1540 mm outside leg dimensions 2480 mm overall height; 2 +2 leaves 1940 mm outside leg dimensions 2480 mm overall height
Fixed corner post	100 x 100 mm square; permanent 90-degree intersection
Overall height	2480 mm =40 head +2400 module grid +40 sill
Leaf profiles	70 mm thermally broken aluminum; charcoal powder coat
Insulating glass build	6 mm glass +12 mm sealed airspace +6 mm glass =24 mm
Operating layout	Two pairs fold toward separate outer jambs; two track/sill sets
Supply unit	One corner opening: four leaves, one post, two frames and itemized hardware

Leaf module and outside leg

800 mm leaf modules: 2 +2 leaves 1740 mm outside leg dimensions 2480 mm overall height

700 mm leaf modules: 2 +2 leaves 1540 mm outside leg dimensions 2480 mm overall height

900 mm leaf modules: 2 +2 leaves 1940 mm outside leg dimensions 2480 mm overall height

Corner Door Order Configuration

Plan: Two leg dimensions, post location, module width and folding direction

Frames and glass: Profile section, charcoal finish, 6/12/6 glass and safety schedule

Operation: Two head/sill runs, hinges, carriers, guides, locks and seals

Installation and delivery: Structural fixing, floor levels, stack space, sequence labels and packing