# Ducted Under-Cabinet Range Hoods with Removable Mesh Filters

**Product Specification Schedule**

| | |
|---|---|
| **Body material** | 0.8 mm brushed 304 stainless steel sheet |
| **Configuration options** | 900 W x 500 D x 150 H mm body two 385 x 300 mm mesh cassettes; 600 W x 500 D x 150 H mm body two 235 x 300 mm mesh cassettes; 750 W x 500 D x 150 H mm body two 310 x 300 mm mesh cassettes |
| **Common body depth and height** | 500 D x 150 H mm |
| **Top exhaust collar** | 150 mm round; 50 mm above body top |
| **Total collar envelope height** | 150 body +50 collar =200 mm |
| **Filter construction** | Two removable aluminum mesh cassettes; 300 mm depth |
| **Electrical configuration** | 220-240 V /50 Hz /single-phase; fan controls and two task lights |
| **Supply unit** | One hood, blower, two filters, lights, collar and mounting package |

**Hood width and filter size**

900 mm hood: 900 W x 500 D x 150 H mm body two 385 x 300 mm mesh cassettes

600 mm hood: 600 W x 500 D x 150 H mm body two 235 x 300 mm mesh cassettes

750 mm hood: 750 W x 500 D x 150 H mm body two 310 x 300 mm mesh cassettes

**Ducted Hood Order Configuration**

Appliances: Kitchen reference, 600/750/900 width and unit count

Components: Stainless body, blower, two mesh filters, controls, lights and fixings

Interfaces: Cooktop clearances, duct route, required fan duty and electrical documents

Delivery: Unit labels, stainless/collar protection, spare filters, set counts and destination