Glass-Door Undercounter Beverage Refrigerators

Product Specification Schedule

Cabinet type	Single glass-door undercounter beverage refrigerator
Configuration options	120 V 60 Hz single-phase cord, plug and electrical component set; 220-240 V 50 Hz single-phase cord, plug and electrical component set
Overall selected envelope	595 W x 570 D x 820 H mm
Interior shelf package	Four adjustable wire shelves plus lower floor storage
Door assembly	Clear double-glazed door, dark perimeter, hinges, seals and bar handle
Cabinet and liner	Coated-steel outer cabinet with white polymer liner
Ventilation and control	Front base grille; independent inlet/outlet routes; single-zone electronic controller
Supply unit	One refrigerator with four shelves, door fittings and selected electrical package

Beverage Cabinet Electrical Package

120 V / 60 Hz Package: 120 V 60 Hz single-phase cord, plug and electrical component set

220-240 V / 50 Hz Package: 220-240 V 50 Hz single-phase cord, plug and electrical component set

Beverage Refrigerator Order Scope

Appliance: Cabinet, glazed door, seals, handle, hinges, controller and base grille

Interior: Four wire shelves, supports and selected lower compartment arrangement

Electrical: Chosen voltage/frequency, cord, destination plug and appliance documentation

Site interface: Opening, door sweep, ventilation route, service access and installation schedule

Configuration basis and sources

Sub-Zero Undercounter Series Design Guide support page - https://www.subzero-wolf.com/assistance/answers/sub-zero/common/subzero-uc-undercounter-and-uw-undercounter-wine-series-design-guide