68 Series Thermal Break Aluminum Folding Glass Door

A thermally broken aluminum bi-fold door that opens a living room fully to a terrace. The 68 Series uses 6063-T5 profiles with a 1.6 mm wall, takes single or double tempered glass, and folds inward or outward.





Specifications

System	68 Series folding door
Frame system	Thermal break aluminum
Alloy	6063-T5 aluminum
Profile wall	1.6 mm
Glazing	Single or double tempered glass, 5, 6, 8 or 10 mm panes
Folding direction	Inward or outward
Accessories	Included with the system
Minimum order	Made to your project quantities. Small item counts are accepted when they ship with the rest of your project list; the quotation confirms the quantity for each item.
Standards & certificates	Tell us the standards or certificates your market or project requires, and we confirm in writing which documents are available for this configuration before you order.

How We Quote the 68 Series

Made to each opening
Each door is made to its opening. The quotation lists every opening with its size, panel count, folding direction and glass.

Accessories included
The system accessories are supplied with each door.

Glass options priced
Single and double tempered glass, and each pane thickness, are priced per opening so you can compare.

With other windows and doors
Windows and sliding doors for the same building can be quoted in one order and shipped together.

What to Send for a Quote

Openings
Width × height per opening

Folding
Inward or outward, stack side

Glass
Single or double, pane thickness

Delivery
Destination port or site