XLS40 Enclosed Linear LED Batten Light

Product Specification Schedule

Fixture body	XLS40 enclosed linear LED batten; white ABS + PC assembly.
Configuration options	XLS40, 40 W integrated LED, 4000 K, white ABS + PC body; nominal 4000 lm and CRI 80.; XLS40, 40 W integrated LED, 6500 K, white ABS + PC body; nominal 4000 lm and CRI 80.
Light-source schedule	Integrated LED included; 40 W nominal input; 4000 lm nominal flux; CRI 80. No beam angle, dimming or emergency function assigned.
Overall dimensions	1205 L x 83 W x 75 H mm. Fixing centers and cable-entry dimensions follow the actual offered assembly.
Electrical listing	110-220 V listed supply; actual voltage version, frequency, driver/control and connection requirements recorded for the destination.
Enclosure and installation	Listed IP65. Complete cable entries, connections, fixing details and cover access are coordinated with the project.
Supply scope	Fixtures by CCT and quantity; named mounting/connection parts, sample, documents, packing, freight and installation separately scheduled.

Light color / CCT

4000 K: XLS40, 40 W integrated LED, 4000 K, white ABS + PC body; nominal 4000 lm and CRI 80.

6500 K: XLS40, 40 W integrated LED, 6500 K, white ABS + PC body; nominal 4000 lm and CRI 80.

XLS40 Batten-Light Quote Schedule

Fixtures: XLS40, 40 W, CCT allocation, electrical version and quantities.

Mounting and wiring: Only named fixing, support and connection parts; field wiring and labor separately stated.

Controls and documents: Any supported control/emergency version, energized sample and required assembly-specific documents.

Packing and freight: Fixture labels, carton data, actual shipment weight, destination and delivery responsibilities.

Configuration basis and sources

XLS40 Enclosed Linear LED Batten | George Light - https://georgelight.com/product/led-tube-light-three-proof-lamp-xls40/

George Light Product Catalog, page46 - XLS-40-N12-40W - https://www.georgebuild.com/wp-content/uploads/2025/12/lights-product-catalog.pdf