ADM302 Surface-Mounted Reflector Spotlight

Product Specification Schedule

Model and body	ADM302; surface-mounted white Aluminum + Acrylic spotlight.
Configuration options	ADM302, 7 W integrated LED, 3000 K; white body, 560 lm, CRI 80, 24 deg beam.; ADM302, 7 W integrated LED, 4000 K; white body, 560 lm, CRI 80, 24 deg beam.; ADM302, 7 W integrated LED, 6000 K; white body, 560 lm, CRI 80, 24 deg beam.
Optical schedule	7 W integrated LED included; 560 lm; CRI 80; 24 deg beam.
Overall dimensions	85 mm diameter x 70 mm height; fixing centers and cable entry follow the offered assembly.
Electrical listing	110-265 V; actual voltage version, frequency, driver/control and connections scheduled for the destination.
Enclosure and mounting	Listed IP20; surface mounting. Supporting ceiling and complete connection detail coordinated with the project.
Order scope	Fixtures by CCT and quantity; named mounting parts, samples, documents, packing and freight separately scheduled.

Light color / CCT

3000 K: ADM302, 7 W integrated LED, 3000 K; white body, 560 lm, CRI 80, 24 deg beam.

4000 K: ADM302, 7 W integrated LED, 4000 K; white body, 560 lm, CRI 80, 24 deg beam.

6000 K: ADM302, 7 W integrated LED, 6000 K; white body, 560 lm, CRI 80, 24 deg beam.

ADM302 Spotlight Quote Schedule

Fixtures: ADM302, CCT, quantity and electrical version by room.

Mounting parts: Named fixing/support and connection parts with quantities.

Control and sample: Any supported control version, energized sample and required documents.

Delivery: Packing, spares, freight destination and installation scope.

Configuration basis and sources

Led Surface Spotlight-ADM302 | George Light - https://georgelight.com/product/led-surface-spotlight-adm302/

George Light Product Catalog - page 43, AD-M302-S7W - https://www.georgebuild.com/wp-content/uploads/2025/12/lights-product-catalog.pdf