Compact Recessed LED Panel Lights, Round & Square

Product Specification Schedule

Model family	LFRO120A round / LFSQ120A square; white Aluminum + Acrylic; recessed mounting.
Configuration options	LFRO120A; 120 mm diameter x 10 mm height; cutout 105 mm diameter; 6 W; 3000 / 4000 / 6000 K.; LFSQ120A; 120 x 120 x H10 mm; 105 x 105 mm cutout; 6 W; 3000 / 4000 / 6000 K.
Light source	Each: integrated LED included; 6 W; 540 lm; CRI 70.
Body and cutout	Round: 120 mm diameter x 10 mm height, cutout 105 mm diameter. Square: 120 x 120 x 10 mm, cutout 105 x 105 mm.
Electrical	Each: 170-265 V listed; actual supply version, driver, frequency and controls scheduled for the project.
Installation	Listed IP20. Driver space, ceiling thickness, opening tolerance and clip access follow the offered assembly.
Supply scope	Model/CCT quantities, included drivers and clips, connection parts, samples, documents and freight identified separately.

Panel shape

Round - LFRO120A: LFRO120A; 120 mm diameter x 10 mm height; cutout 105 mm diameter; 6 W; 3000 / 4000 / 6000 K.

Square - LFSQ120A: LFSQ120A; 120 x 120 x H10 mm; 105 x 105 mm cutout; 6 W; 3000 / 4000 / 6000 K.

Recessed Panel Quote Schedule

Panel lines: LFRO120A or LFSQ120A, CCT, quantity and electrical version.

Included parts: Named drivers, clips and connection accessories with quantities.

Samples: Shape/fit and energized sample; required version-specific documents.

Delivery: Carton labels, spare quantities, packing and freight destination.

Configuration basis and sources

Panel Lamp-LFRO120-A | George Light - https://georgelight.com/product/panel-lamp-lfro120-a/

Ceiling Light Panels-LFSQ120-A | George Light - https://georgelight.com/product/ceiling-light-panels-lfsq120-a/

George Light Product Catalog - page 46, LF-RO120-A-6W / LF-SQ120-A-6W - https://www.georgebuild.com/wp-content/uploads/2025/12/lights-product-catalog.pdf